

DM1424

Hematocrit Centrifuge

Features

- Speed range of 200–12000 rpm Precise and independent control of speed and time
- Easy operation with intuitive menu and LCD display
- Maintenance-free brushless DC motor
- Pulse operation for fast and convenient quick spins
- Advance features include speed/RCF switch; short-time run function; audible alert function
- Safety features include door interlock, overspeed detector; over-temperature detector; automatic internal diagnosis and automatic rotor identification



DM1224

Economical Hematocrit Centrifuge

Features

- Speed range of 500–12000 rpm
- Precise control of speed and time
- Maintenance-free brushless DC motors
- Door interlock

Applications

DLAB hemocrit centrifuges are used for determination of erythrocyte fractions in blood as well as micro solution separations. It provides hemocrit values (HCT) for testing in biochemistry, immunity, genetics, blood separation and for general clinical tests for diagnostic purposes and also for dope tests. They have special applications for the photometric determination of bilirubin content in neonate blood samples. They are suitable for extraction of DNA and RNA. Veterinary clinics and Vitamins testing for Infants.



Specifications	DM1424	DM1224
Speed Range	200–12000rpm, increment: 10rpm	500–12000rpm, increment: 100rpm
Max. RCF	13680 × g	13680 × g
Speed Accuracy	± 20	± 100
Run Time	30sec–99min/Continuous	10sec–99min/Continuous
Motor	Brushless DC motor	Brushless DC motor
Display	LCD	LCD
Safety Devices	Door interlock, Overspeed detector; Automatic internal diagnosis, Automatic rotor identification	Door interlock
Acceleration/Braking time	30s ↑ 30s ↓	40s ↑ 40s ↓
Power Requirements	Single-phase, 200V–240V, 50Hz/60Hz, 5A; 100V–120V, 50Hz/60Hz, 5A 160W	Single-phase, 200V–240V, 50Hz/60Hz, 5A; 380W
Dimension[WxDxH]	280 × 364 × 274mm	280 × 364 × 213mm
Weight	10.5kg	8.5Kg
Certification	CE cTÜVus FCC MCA	–
Advanced features	Speed/RCF switch; Short-time run function; sound-alert function	Speed/RCF switch; Short-time run function; sound-alert function



Available rotors

AC24

Cat. No.19400047

DM1424 & DM1224

Max. speed: 12000rpm

Max. RCF: 13680 × g

Rotor capacity: capillary tubes x24

Rotor material: High strength aluminum

